

KOTEBAT

LOGIC

DOOR PANELS

aluminium panel solutions from PORTALUXE



PORTALUXE
Designed by PortaXXI

LOGIC DOOR PANELS



LOGIC **VC 01**



LOGIC **VC 02**



LOGIC **VC 03**



LOGIC **VC 04**



LOGIC **VC 05**



LOGIC **VC 06**



LOGIC **VC 07**



LOGIC **VC 08**



LOGIC **VC 09**

Handle | Puxadores | Tirant | Türgriffe:



PX01 Ø 25 mm length 300 mm	PY01 □ 20 x 40 mm length 500 mm	PZ01 □ 20 x 40 mm length 1400 mm	PX02 Ø 25 mm length 657 mm	PX03 Ø 25 mm length 1500 mm	PQ01 □ 30 x 30 mm length 600 mm	PQ02 □ 30 x 30 mm length 1400 mm
---	--	---	---	--	--	---



TECHNICAL FEATURES

Composition:	1,5 mm aluminum sheet + injected polyurethane + 1,5 mm aluminum sheet
Available finishings:	· RAL lacquered · anodized · Renolit
Panel thickness:	20 mm , 24 mm, 28 mm, 30 mm, 34 mm
Polyurethane density:	120kg/m ³
Dimensions:	· 2000 x 800 mm · 2100 x 900 mm others upon request
Double glazing:	Frosted glass, others upon request

Reserves the right to make any change without notice.
Possible colour deviations are due to the printing technology.



CARACTÉRISTIQUES TECHNIQUES

Composition:	1,5 mm aluminium tôle + polyuréthane injecté + 1,5 mm aluminium tôle
Finitions disponibles:	· RAL laqué · anodisé · Renolit
Epaisseur du panneau:	20 mm , 24 mm, 28 mm, 30 mm, 34 mm
Densité de polyuréthane:	120kg/m ³
Dimensions:	· 2000 x 800 mm · 2100 x 900 mm autres sur demande
Double vitrage:	Sablé, autres sur demande

Nous nous réservons le droit d'apporter des modifications sans préavis. Possibilité d'écarts de couleurs dû au système d'impression.



CARACTERÍSTICAS TÉCNICAS

Composição:	1,5 mm chapa de alumínio + poliuretano injectado + 1,5 mm chapa de alumínio
Acabamentos disponíveis:	· RAL lacado · anodizado · Renolit
Espessura do painel:	20 mm , 24 mm, 28 mm, 30 mm, 34 mm
Densidade poliuretano:	120kg/m ³
Dimensões STD:	· 2000 x 800 mm · 2100 x 900 mm outras sob consulta
Vidro duplo:	Fosco, outras sob consulta

Reservamos o direito de efectuar qualquer modificação sem aviso prévio. Possíveis desvios de cor, devido à tecnologia de impressão.



TECHNISCHE ANGABEN

Ausführung:	1,5 mm Aluminiumdeckschicht + injiziertes Polyurethan + 1,5 mm Aluminiumdeckschicht
Wählbare Oberflächen:	· RAL lackiert · eloxiert · Renolit-Folienbeschichtung
Füllungsstärke:	20 mm , 24 mm, 28 mm, 30 mm, 34 mm
Polyurethandichte:	120kg/m ³
Lieferbare Maße:	· 2000 x 800 mm · 2100 x 900 mm andere auf Anfrage
Doppelverglasung:	Satinato, andere auf Anfrage

Wir behalten und das Recht vor, ohne vorherige Ankündigung, Änderungen vorzunehmen. Eventuelle Farbabweichungen sind drucktechnisch bedingt.

KOTEBAT

13 400 AUBAGNE - FR
Tel : +33 442 189 142
Fax : +33 442 189 285
Email: info@kotebat.fr



PORTAXXI, SA.
www.portaluxe.com.pt
geral@portaluxe.com.pt

Parque Industrial de Adaúfe, Lote 9
Apartado 2020
4710 - 571 Braga, Portugal

Tel.: 00 351 (0) 253 670 242
Fax: 00 351 (0) 253 628 357